

DIGITAL PORTABLE PROCESS DATALOGGER

HTLOG - 742 (Portable)

- Portable, battery Powered
- Low power Consumption
- Display for both % Rh and Temperature
- Compact ABS Cabinet

FEATURE HIGHLIGHTS

- Direct Reading in case of % RH & Temperature
- 16 Bit ADC
- Resolution Selectable
- Alphanumeric LCD Display with back lit
- RS232 Interface with Windows Software
- Printer port
- Displays 2Channel Simultaneously
- Data logger with 4000 Records Per Channel
- Real Time Clock

RS ENTERPRISES HTLOG 742T series data logger/Indicator are digital electronic marvels is a power full Datalogger. The unit can store 4,000 records per channel at the programmed interval. You can store as many data sets as you want until memory is full. The unit comes with windows-based software (windows98, NT, XP) for the display & saving.



HTLOG-742TH is a combined unit for measuring temperature & Humidity are in fact two instruments combined into one compact unit for direct reading in case of relative humidity (%RH) & dry bulb temperature without the need to select different probes. The high quality HYGROCLIPSensor module for measuring Relative humidity & temperature is 100 % Exchangeable with out readjustment which offers advantage of no loss of time in recalibrating & readjusting.

Specifications

HTLOG-742T

Input: -2 Channels, PT-100 RTD, 3 Wire

Range: $-100 \text{ to } +300^{\circ}\text{C}$

Resolution: - 0.1/0.01°C (Selectable)

Accuracy: - +/-0.2 % F.S.D

Display: - Yellow Co lour LCD Display with Backlit

Sample Rate: -3 Seconds
Operating Conditions

0 to 50°C

0 to 80 % RH Non Condensing

Zero Drift

Nil: -Automatically Corrected By A/D converter

Warm Time; - Instantaneous

Power Supply: -9Vdc Battery (1 or 2 optional) or AC

adapter

Dimensions (In mm)

Over all: (LXHXD) 66X155X25

Weight 1000gms

HTLOG-742TH

Input: - 0 to 1 Vdc

Range: - Temp -40 to $+60^{\circ}$ C , RH: - 0 100 %

Resolution: - 0.1/0.01°C (Selectable)

TYPE OF SENSOR: - Hygroclip

R. S. ENTERPRISES

Specialist's in Instrumentation

SHREE RAM COMPLEX, NO. 1126 /1, MODEL COLONY, SHIVAJINAGAR, PUNE 411 016.

PUNE 411 016.

TEL.: 91-20-2565 3315 / 2565 1316

FAX: 91-20- 2567 7202 Email : rse4in@yahoo.co.in Visit us at : www.rsentp.com Subject to change without prior notice.