



HUMITHERM942 series

ORDERING INFORMATION

Humitherm:- 942XHTX Temperature /Humidity Transmitter



X= Mounting Option
 Where W= Wall mount
 D= Duct Mount
 S= Space mount
 D1= Display



Other Products

PORTABLE DATA LOGGER



- 3 Volt Battery Operated
- 65000 Record each
- Battery life 2 Months
- Calibration facilities available
- USB interface

DIGITAL CLEAN ROOM MONITOR



ADVANCED MEASUREMENT TECHNOLOGY WITH RS 485/4-20mA output for DDC Controller

Features :

- The RS51 is specifically designed for the monitoring of Clean Rooms and packaged in a compact shallow enclosure allow installation in prefab Clean Room Panels of thickness 40mm or more
 Software calibration for all 3 channel with password protection
- Programmable Alarm Limits with Visual Annunciation
 - Records Max and Min Values
 - **Internal Data Logging up to 1000 logs***
 - Confirms to 21 CFR11 requirements.
 - Fits into standard 112 mm circular cutout.
 - Microprocessor based design with LCD display advanced fault tolerant design.

RH, TEMPERATURE & DP IN FLAMEPROOF



Available with **remote H+Temperature Sensor** in FLP Enclosure

- 21 CFR Part 11 compliant
- Display RH, Differential Pressure & Temperature
- High Accuracy
- Input Compatible with most RH Sensors, PT100 & 0-10V & 4-mA Transmitters